



ALLIN PRIME OKOUME



ARBOR

ALLIN
La Motte Michel, 79270 Le Vanneau
Tel. : +33 (0)5 49 35 15 82
contact.allin@groupe-arbor.com
www.allin.fr



FACES	Peeled Okoume veneers 10/10 ^{ths} Faces quality B/BB
INNER LAYERS	Standard plies - 100% Okoume
GLUE	Class 3 - Outdoor use Glue Standard EN 314
DIMENSIONAL TOLERANCE	Standard EN 315
DENSITY	500 kg/m ³ (+/- 10%). Standard EN 323




E1

CE₂₊



RECOMMENDED APPLICATIONS



Indoor
& outdoor
joinery



Cladding



Outdoor
ceiling



Roof soffits
& edges



Indoor
& outdoor
furniture

BENEFITS

Good resistant to moisture
Naturally durable

Timesaving (painted with white UV 100g
paint on 2 sides)



The mark of
responsible forestry

DIMENSIONS (MM)		THICKNESS (MM)					
		10	12	15	18	22	25
2500 x 1220	No. of plies	5	7	7	9	9	11
	Pack size*	48	48	32	32	16	16
3100 x 1530	No. of plies	5	7	7	9	9	11
	Pack size*	50	50	25	25	25	25

* quantity per pack may vary within the scope of +/-10%